

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Problem Image Mailbox.**

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 0 634 674 B1

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention
of the grant of the patent:
24.03.1999 Bulletin 1999/12

(51) Int Cl.⁶: G02B 5/30, G02F 1/1335

(21) Application number: 94304539.3

(22) Date of filing: 22.06.1994

(54) **Optical assembly with high efficiency chiral nematic LC polarizer**

Optischer Aufbau mit hocheffizientem chiral nematischem Flüssigkristallpolarisator
Assemblage optique avec polariseur à haute efficacité avec cristal liquide nématique chirale

(84) Designated Contracting States:
BE DE DK FR GB IT NL SE

(30) Priority: 29.06.1993 US 84634

(43) Date of publication of application:
18.01.1995 Bulletin 1995/03

(73) Proprietor: KAISER AEROSPACE &
ELECTRONICS CORPORATION
Foster City, California 94404 (US)

(72) Inventor: Kalmanash, Michael H.
Los Altos, CA 94204 (US)

(74) Representative: Maggs, Michael Norman et al
Kilburn & Strode
20 Red Lion Street
London WC1R 4PJ (GB)

(56) References cited:
WO-A-91/06889

US-A- 5 221 982

- SID 90 DIGEST, 15 May 1990, LAS VEGAS, US pages 110 - 113 MAURER ET AL 'Polarizing Color Filters made from Cholesteric LC Silicones'
- JAPANESE JOURNAL OF APPLIED PHYSICS, vol.29, no.10, October 1990, TOKYO JP pages 1974 - 1984 SCHADT ET AL 'New Liquid Crystal Polarized Color Projection Principle'
- JOURNAL OF FUSION ENERGY, vol.5, no.1, 1986, NEW YORK US pages 65 - 75 JACOBS 'Liquid Crystal Devices for Laser Systems'
- OPTOELECTRONICS DEVICES AND TECHNOLOGIES, vol.7, no.2, December 1992, TOKYO JP pages 263 - 270 FÜNFSCILLING ET AL 'The Efficient Optics of Liquid Crystal Polarized Color Projection'
- PATENT ABSTRACTS OF JAPAN vol. 17, no. 390 (P-1577) 21 July 1993 & JP-A-05 066 503 (FUJITSU) 19 March 1993

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

D scription

I. FIELD OF THE INVENTION

[0001] The present invention relates to display devices and, more particularly, to high efficiency polarizers in applications such as active matrix liquid crystal (LC) displays.

II. BACKGROUND OF THE INVENTION

[0002] In the prior art, the brightness of a liquid crystal display (such as a computer terminal screen) has been adversely affected by absorptive elements in the optical path. For example, the front and rear polarizers in a conventional twisted nematic liquid crystal display assembly can absorb more than two thirds (2/3) of the overall luminance emitted by the backlight. Display brightness can be enhanced by ensuring that more light is transmitted, either by increasing the backlight intensity or reducing the amount of light lost in the absorptive elements.

[0003] Increasing the backlight intensity has the major drawbacks of higher power dissipation (leading to shortened battery life for portable equipment) and shortened backlight bulb life. Although power dissipation and battery size and life are ever present challenges, the prior art fails to consider a closer examination of the absorptive elements in backlit "direct view" liquid crystal display applications, i.e. computer screens or televisions, with the goal of reducing the absorption conventional polarizers are made from stretched polyvinyl alcohol films containing iodine (or a dye if color is desired) between layers of cellulose acetate, attached to a glass surface with an acrylic adhesive and covered by a layer of plastic. Transmission does not exceed 40%, efficiency is lost over time, and polarizers are an expensive component in the manufacture of LCDs. According to the present invention, in a direct view application (such as a computer or television screen), the conventional rear polarizers are replaced with a high efficiency, non-absorptive chiral nematic liquid crystal polarizer whose transmissiveness is substantially greater than the absorptive polarizers of the prior art.

A. Liquid Crystal (LC) Polarizers

[0004] The concept of liquid crystal devices (LCDs) as display elements is familiar. The effect of electrical current through an LC display element backlit with polarized light produces the well-known "black line segments" which are featured in everything from digital watch displays to laptop computer screen text. By contrast, the application of a liquid crystal as a polarizer is not at all familiar or common. Before discussing the scant prior art which discusses liquid crystal polarizers, an overview of the characteristics of cholesteric liquid crystals (CLCs) is necessary to provide a basis for illus-

trating the present invention.

B. Cholesteric Liquid Crystal (CLC) Polarizers

[0005] Cholesteric liquid crystals (CLCs) are a class of liquid crystals exhibiting unique optical properties. Cholesteric liquid crystals were originally so named because the substances in which the pattern of molecular ordering was observed were related to cholesterol, hence "cholesteric". The more descriptive terminology for this class of liquid crystal is "chiral nematic". "Chiral", meaning "twisted", and "nematic", meaning "thread", succinctly express the gross appearance of the molecular orientations: like twisted threads. Popular and technical literature still frequently refer to the class by its early name. For the purposes of this discussion, however, the terms "cholesteric" or "chiral nematic" liquid crystal or "CLC" or "CNLC" will be used interchangeably, with the intention that each term be understood to include the entire class of chiral nematic liquid crystals.

[0006] The distinct helical molecular ordering imparts CLCs with several notable optical properties. First, CLCs are virtually non-absorptive. Light hitting a CLC is either transmitted or reflected. Second, CLCs exhibit circular dichroism for certain wavelengths of light. By way of explanation, consider the concept of polarization. While it is familiar to most to consider light as being either horizontally or vertically (linearly) polarized it is useful and viable to alternatively conceptualize light as composed of two possible circular polarizations - right and left. Light can thus be conceived of as composed of righthanded and lefthanded circular polarizations. A chiral nematic liquid crystals allows wavelengths of light that are significantly longer or shorter than the mean refractive index of the liquid crystal multiplied by its pitch (the distance in which the liquid crystal molecular helical structure completes one complete twist) to simply pass through the liquid crystal. For wavelengths of light that are at or near the product of refractive index and the pitch, however, the interaction of the chiral nematic liquid crystal structure and the light's circular polarization is much like twisting a nut onto a screw. Light of the same polarization sense or handedness passes easily, like a right handed nut easily screws onto a right handed screw. However, light of the opposite polarization is reflected. This phenomenon of "selective reflection" as well as the characteristic non-absorption accounts for the virtual fifty percent transmission of incident light with a wavelength equal to the CLC pitch multiplied by the material refractive index.

[0007] This effectively optimal percentage of transmitted circularly polarized light is a vast improvement to the ultimate brightness of the active matrix liquid crystal display since it is only polarized light which eventually contributes to the screen images displayed to the viewer.

[0008] The band of light wavelengths subject to circular dichroism is a characteristic of the material used in the CLC polarizer, and is referred to as the device's

"notch" or "notch bandwidth" Light wavelengths within the "notch" region will be circularly polarized by the CLC device and either transmitted or reflected. Light outside the "notch" is transmitted by the CLC. Only light in the "notch" region contributes to the display that is seen by the viewer of a direct view device, and therefore it is important that the "notch" region be broad enough to cover the full spectral range of the LCD backlight.

[0009] In short, the instant invention effectively eliminates the absorption problem heretofore inherent in conventional polarizers since the CLC does not absorb any appreciable amount of light. On an initial pass, nearly 50% of light in the notch bandwidth is circularly polarized on passing through the CLC polarizer, passes through a quarter wave plate where it becomes linearly polarized, and, ultimately, "feeds" the display.

C. Notch, Bandwidth and Birefringence

[0010] As it is apparent from the above discussion, the notch bandwidth of a CLC determines how broad a band of light wavelengths the CLCs will polarize. The notch or notch central wavelength (λ_0) is related to the device properties by the equation

$$(1) \quad \lambda_0 = n \times p \times \cos \theta$$

where "n" is the average refractive index of the liquid crystal material, "p" is the helical pitch of the chiral nematic material, and "θ" is the angle of the incident light. For normally incident light, the equation reduces to

$$(2) \quad \lambda_0 = n \times p$$

[0011] The notch central wavelength (λ_0) is directly related to the liquid crystal's pitch (p).

[0012] The polarization (notch) bandwidth can be approximately expressed as

$$(3) \quad \Delta\lambda = \Delta n \times p$$

where "Δn" is the birefringence of the material. From this equation it can be seen that polarization bandwidth (Δλ) is directly related to material birefringence (Δn). Chiral nematic liquid crystal materials can be designed for high birefringence (Δn) and correspondingly broad width (Δλ). Since the CLC device is highly transmissive outside its "notch", multiple CLC devices (with different λ_0 's) can be stacked to provide a broadband polarizer. However, a single broad notch bandwidth reduces the number of discrete components needed for broadband optical systems. The invention herein teaches a liquid crystals film or films of sufficiently broad bandwidth so as to polarize and transmit light of the entire visible spectrum (450 nm to 650 nm). As discussed below, it is the

polymer chiral nematic liquid crystal which exhibits the optical and physical properties necessary for the invention taught herein.

1. Chiral Nematic LCs: Monomers Versus Polymers

[0013] Monomer CLCs used in a variety of applications differ markedly from a polymer chiral nematic LC used as a polarizer, largely due to the differences arising from monomer versus polymer structure.

[0014] Monomer LCs are made up of short, single chain molecules. Polymer LCs are made up of long chain molecules consisting of a sequence of repeating monomers which are connected by chemical bonds. In the polymers of the invention, the properties are derived from monomer LCs attached to a polymer backbone.

[0015] The polymer's physical and optical properties are quite different from those of the ubiquitous monomer. Because the optical properties of monomer LCs are typically defined in narrow spectral ranges, monomers are brilliant (due to the high transmissiveness/low absorption) but monochromatic (due to the narrow notch bandwidth). Polymer chiral nematic LCs can be designed with broad optical properties - making them more achromatic and, therefore, adaptable to full color displays. So too, monomers are typically extremely temperature sensitive and the related optical properties are temperature dependent (hence the popular use in the thermometers). Polymer liquid crystals, however, have excellent thermal stability over a wide range of temperatures. Moreover, polymers also demonstrate environmental durability owing to a "frozen" mesophase at temperatures below 150 degrees C. Polymer chiral nematic liquid crystals also exhibit stable optical properties over a wide temperature range.

[0016] Another major difference between monomers and polymers is that, owing to the different physical properties, polymer chiral nematic liquid crystals can be fabricated as free-standing films or can be spread on a single glass substrate layer. Monomers, on the other hand, are found only in a relatively low viscosity (liquid) state, and therefore must be confined in a glass "cell", in which two sheets of glass contain the liquid crystal. The cell is sealed around the entire perimeter to keep the liquid crystal from leaking out.

[0017] A free-standing polymer chiral nematic liquid crystal film (which may be imagined as a plastic-like sheet) is dramatically lighter than the conventional double glass cell required for monomer liquid crystals. Alternatively, and in the interests of greater durability, a single glass substrate can be used to support a thin polymer chiral nematic liquid crystal film. As the present invention teaches, even the use of a single glass substrate can achieve a significant weight savings over either a conventional or monomeric polarizer.

2. Monomer Projection polarizers

[0018] While polymer chiral nematic crystals ("CN-LC") are discussed in the literature, for example in the article by R. Maurer, et al., in the SID 90 Digest, pages 110-113, which discloses the use of cholesteric LC-Silicones in polarizing filters, they have not been associated with display applications. Recent literature discusses application of monomer chiral nematic liquid crystal devices in a projection system such as might be suitable for high definition television. (Schadt, Martin and Fünfschilling, Jurg, "Novel Polarized Liquid Crystal Color Projection and New TN-LCD Operating Modes" SID 90 DIGEST p. 324-6). Schadt and Fünfschilling describe a system which uses three narrow bandwidth monomer LC polarizers tuned to red, green, and blue, respectively, to generate the projection display colors from the white display backlight. Id.

[0019] In another article by Schadt and Fünfschilling in the Japanese Journal of Applied Physics, Volume 29, No. 10, October 1990, pp 1974-1984, titled "New Liquid Crystal Polarized Color Projection Principle", a projection system is disclosed. This projection system includes a light source, a cholesteric filter adjacent the light source and a rear mirror adjacent the light source and for reflecting light from the light source. Polarized transmission occurs in the cholesteric filters only over a limited bandwidth. Adjacent the cholesteric filter is a quarter wave plate for converting circularly polarized radiation so linearly polarized radiation, adjacent which is an LCD.

[0020] The current invention deals not with projection, but with a direct view device, and employs a polarizer composed of broadband polymer chiral nematic liquid crystal devices, as opposed to monomer liquid crystals.

[0021] Hence, the invention herein disclosed is remarkably different from any device to date. Monomer liquid crystal devices typically have polarization (notch) bandwidths (usually less than 20 nm). The system described by Schadt supra uses three narrow bandwidth chiral nematic liquid crystal polarizers, tuned to red, green and blue, to generate the projection display colors from the white display backlight.

[0022] The invention herein discloses a device utilizing one or more polymer liquid crystal films, each of which has a broad bandwidth and, consequently, properly arranged, can create a film which transmits the entire visible spectrum (450nm to 650nm).

[0023] Moreover, the disclosed direct view application differs significantly from the prior art projection devices. The projection device used by Schadt was, arguably, suitable for viewing because the light through the monomer chiral nematic liquid crystal polarizer is collimated (i.e. in parallel beams). This had the practical effect of producing a projected image which appeared fairly stable to the viewer.

[0024] A monomer liquid crystal is unacceptable as a rear polarizer for a direct view display, such as computer

terminal. Because the polarization "notch" is a function of viewing angle, in a narrowband monomer LC polarizer for direct view, the polarizer notch(es) would appear to shift at the slightest position change of the viewer and, consequently, the polarization efficiency at the wavelength emitted by the backlight would suffer and the contrast of the computer screen would be markedly reduced, depending upon the viewer's position. Two persons watching the same computer game, for instance, would each see different image quality since they each experience different viewing angles. This so limits the usefulness of a direct view color display that monomers are not candidates for polarizers in a LC direct view display.

[0025] The polymer liquid crystal disclosed herein is free of this serious shortcoming because it has a broader bandwidth and produces an achromatic display that does not shift in color as the viewer changes viewing angle. Thus, two persons playing a computer game on an assembly employing the herein disclosed invention would each see similar quality.

III. SUMMARY OF THE INVENTION

[0026] The current invention concerns the use of broadband polymeric chiral nematic liquid crystal ("CN-LC") films as high efficiency polarizers in liquid crystal displays ("LCDs") and similar applications.

[0027] According to the present invention, there is provided an optical assembly as specified in claim 1. Some preferred features of the assembly are specified in the dependent claims.

A. Polymer Chiral Nematic LC Polarizer

[0028] According to the present invention, the conventional rear polarizer of a display device is replaced with a transmissible (i.e. non-absorptive) polymer chiral nematic LC polarizer. The polymer chiral nematic LC polarizer is virtually 100% transmissible and the wavelengths of light in the "notch" bandwidth are transmitted as right or left-handed circularly polarized light. Only one "handedness" of light is transmitted in the notch bandwidth; the non-transmitted light is not absorbed but reflected back to the rear reflector backlight housing without reversal of polarization (e.g. incident left-handed light is reflected as left-handed light). Light reflected onto the backlight housing is re-reflected with a portion undergoing a which has reversed its "handedness" in this manner is then the proper orientation for transmission and passes through the polarizer.

[0029] Thus, a portion of the light is then retransmitted through the chiral nematic LC polarizer; light which is not transmitted is re-reflected a second time. The process repeats until a very high percentage of light is eventually transmitted through the CNLC rear polarizer. Despite the multiple reflections light may undergo before it passes through the rear polarizer, very little light is ac-

tually absorbed by the chiral nematic LC polarizer, especially as compared with conventional polarizers.

[0030] Accordingly, one advantage of the current invention is increased net light transmission, leading to increased brightness and/or reduced power dissipation. For many applications (e.g., portable equipment) additional advantages include increased battery operation time and/or reduced battery weight.

[0031] Prior art liquid crystal devices only polarized light within narrow wavelength band. High birefringence (Δn), broad polarization bandwidth ($\Delta\lambda$) liquid crystal polymers can be formulated by attaching chiral and nematic liquid crystal monomers to backbones from the methacrylate/acrylate class of polymers. Products of this process can polarize light across a broad spectral region, enabling a single element polymer cholesteric liquid crystal film to function as a wide band polarizer. Practically speaking, this combination of physical and optical properties translates into smaller, lighter, brighter devices (e.g. full color portable televisions or computer screens).

[0032] Alternatively, multiple polymer cholesteric liquid crystal films, can each be constructed with a lower birefringence material (Δn) (narrower polarization bandwidth ($\Delta\lambda$) and then could be layered to produce a finished composite film with broad bandwidth. For example, three separate films, respectively tuned to the red, green and blue spectral regions, can be overlaid to produce a broadband polarizer. This, too, produces a device that is smaller, lighter, and brighter than the prior art.

[0033] As with prior art structures, polymer chiral nematic liquid crystal devices can be constructed using two glass substrates with the liquid crystal captured between them. In the process of constructing such an assembly, the substrates are used as forming and aligning elements (the separation distance determining the film thickness) as well as functioning as a support element to the thin polymer cholesteric liquid crystal film in the assembled device. For single substrate device fabrication, the approach includes an initial assembly with two substrates and the liquid crystal between the two, where one substrate is coated with a release film to allow its subsequent disassembly and removal from the liquid crystal. This leaves an assemblage consisting of the single remaining glass substrate and the liquid crystal polymer film.

[0034] For multi-film systems, subassemblies could be integrated into a single assembly by bringing a pair of polymer chiral nematic liquid crystals films into juxtaposition applying pressure, and heating to above the glass transition temperature (T_g) to allow the films to adhere. Alternatively, a thin lamination layer (e.g. Ecogel) could be used as a bonding agent between films. One glass substrate pretreated with a release film enables its removal from the adhered films. The process can be repeated for a plurality of layers. Advantages of this combination include greater durability along with reduced weight and bulk.

B. Backlight Modifications

[0035] In conjunction with the introduction of a chiral nematic liquid crystal rear polarizer as an element in the otherwise conventional display assembly, modifications to the backlight housing may also increase transmission of light, thereby brightening the resulting display. While the first requirement of a backlight housing is that it be highly reflective, the housing's ability to preserve polarization sense (eg. through the use of a metallic reflector) optimally improve net transmission of the overall system when used with a chiral nematic liquid crystal rear polarizer.

[0036] This is explained by considering the fact that light reflected by the chiral nematic liquid crystal polarizer is circularly polarized. When re-reflected from a metallic backlight housing, the light has its sense of polarization reversed (e.g. assuming initially left-hand circular polarization, then the reversal is from left to right-hand circularly polarized). Since the polarizer transmits right-handed polarized light (and reflects left-hand polarized light), the re-reflected light is predominantly right-hand polarized as a result of the reversal and, on a second pass, a larger proportion of the previously rejected light is transmitted by the chiral nematic liquid crystal polarizer than would be the case if the light were randomly polarized. While some slight loss is inherent in each reflective cycle, increasing the light transmission with each cycle enhances the net transmission of the device. The backlight housing reflector also scavenges unpolarized light which is transmitted in the wrong direction.

IV. BRIEF DESCRIPTION OF THE DRAWINGS

[0037] A more complete appreciation of the invention and many of the attendant advantages thereof will be readily obtained as the same becomes better understood by reference to the following detailed description when considered in connection with the accompanying drawings, wherein:

Figure 1 shows the function of a cholesteric or chiral nematic liquid crystal polarizer;

Figure 2, including 2A and 2B, illustrates the notch bandwidth wavelength being transmitted through a chiral nematic liquid crystal polarizer.

Figure 3 shows a conventional display assembly according to the prior art;

Figure 4, including 4A and 4B, illustrates a display assembly according to the present invention;

Figure 5 shows a prior art liquid crystal display cell with two supporting glass plates and a perimeter seal;

Figure 6, including 6A and 6B, shows in detail a polarizer using a polymeric chiral nematic liquid crystal useful in the present invention;

Figure 7 shows a freestanding polymer chiral

nematic liquid crystal film suspended in a partial frame; and

Figure 8 depicts a multifilm polymer chiral nematic liquid crystal polarizer with single glass supporting layer.

V. DETAILED DESCRIPTION OF THE DRAWINGS

[0038] Figure 1 illustrates the function of a cholesteric or chiral nematic liquid crystal polarizer. All electromagnetic radiation outside the notch polarization bandwidth is transmitted without absorption and without polarization. Wavelengths in the notch polarization bandwidth are half transmitted as one-handed circularly polarized and half reflected as the opposite handed circularly polarized light. The figure shows transmission of right hand circularly polarized light and reflection of left hand circularly polarized light.

[0039] Figure 2 illustrates the notch polarization bandwidth of a cholesteric liquid crystal as a transmission plot. Light with wavelengths in the notch bandwidth from λ_1 to λ_2 can be described as having circularly polarized components in both senses or handednesses. One preferred "handedness", right or left, is transmitted and the other is reflected. Figure 2B illustrates the composite bandwidth of three polymer cholesteric liquid crystal films with effectively overlapping bandwidths.

[0040] Figure 3 depicts a conventional prior art display assembly 10 which consists of a light source 12, a rear reflector 14; a rear polarizer 16; a liquid crystal display 18; and a front polarizer 20. Light emitted from the source 12 either is absorbed by the rear polarizer 16 or passes directly through the liquid crystal display 18. Thus, only the light that initially passed through the rear polarizer 16 reaches a viewer 22. A significant portion of the light is lost by absorption by the rear polarizer 16.

[0041] Consequently, to keep the display screen 18 bright, the light source 12 necessarily must consume more electrical power. In applications such as notebook size computers, this means significantly heavier batteries, shorter battery life, shorter backlight life, and increased weight.

[0042] The invention taught herein, as depicted in Fig. 4A, is an assembly 30 of a light source 12 which provides the illumination of the display; a metallic, polarization reversing rear reflector (backlight housing) 32; a rear polarizer 34 composed of a broadband polymer chiral nematic liquid crystal film; a device that converts circularly polarized light to linearly polarized light, such as a quarter wave plate 36; the active (image forming) liquid crystal element 18; and the front polarizer 20. All of the elements are in an alignment normal to the viewing plane with the rearmost component being the metallic reflector 32 and the frontmost, the front polarizer 20.

[0043] Light emitted from the source 12 is transmitted in large part by the broadband chiral nematic LC polarizer 34, in the form of highly circularly polarized light, either left or right handed, but not both. Light oppositely

polarized to that which is being transmitted is reflected to the backlight housing reflector 32 where it is re-reflected.

[0044] Of the re-reflected light, a portion will pass through the chiral nematic LC rear polarizer 34 as circularly polarized light and the remainder (light which is polarized opposite to that which is transmitted) will be re-reflected again from the reflector 32. As seen in Figure 4B, this sequence of transmission of some light and re-reflection of the remainder is repeated until a high percentage of the light is eventually transmitted through the chiral nematic LC rear polarizer 34.

[0045] After passing through the rear polarizer 34, the transmitted light encounters the quarter wave plate 36 which converts the circularly polarized light to linearly polarized light. The linearly polarized light then passes through the active liquid crystal display (LCD) device 18 and the front polarizer 20 before reaching the viewer 22.

[0046] The polarized light is selectively rotated by the LCD (on a pixel-by-pixel basis), under control of an electrical signal, so that it is either in line with, or orthogonal to, the front-polarizer transmission axis. Light which is transmitted through the front polarizer 20 is perceived by the viewer as the bright portion of the display. Non-transmitted light is absorbed by the front polarizer and forms the dark portions of the display image. Since the polymeric chiral nematic liquid crystal 34 polarizes and, hence, transmits light of the entire visible spectrum, the display can be filtered (on a pixel-by-pixel basis) to create full color images.

[0047] The material for the chiral nematic liquid crystal rear polarizer 34 should be chosen for high birefringence since high birefringence results in broad bandwidth. Bandwidth is directly related to the visible spectrum: a bandwidth of, for example, 250 nm, with a central notch wavelength in the center of the visible range (i.e. in the neighborhood of 525 nm) is sufficient to transmit light of the entire visible spectrum.

[0048] The polychiral nematic liquid crystal used in the assembly of the present invention as a notch polarization bandwidth sufficient to allow transmission of circularly polarized light within a 100 nm to 250 nm wide band.

[0049] Materials which form polymer chiral nematic liquid crystals can have birefringence high enough, and, consequently, bandwidth broad enough, to transmit the entire visible spectrum. One class of materials which has demonstrated these high birefringence characteristics is derived from cyanotolane and (S) - (-) - (1) - phenylethanol. Thus, a single broadband/high birefringence liquid crystal film or a combination of films could polarize and transmit all visible wavelengths of light.

[0050] Figure 5 illustrates the conventional, prior art monomeric liquid crystal apparatus 40. Since monomeric liquid crystals 42 are relatively low viscosity liquids, a monomer liquid crystal 42 needs to be fully captured by a cell consisting of two glass substrate layers 44 sandwiching the monomer liquid crystal 42 and a perimeter

seal 46 which prevents leaking of the monomeric liquid crystal 42.

[0051] Figure 6, including Figures 6A and 6B, illustrates the preferred embodiment of the invention taught herein, in particular as to the structure of a rear polarized 50. In Figure 6A, the polymer liquid crystal 52 is initially formed into a film of desired thickness by two glass substrates 54, 56, respectively. Once formed, one of the glass substrates 56 can be removed, as in Figure 6B leaving a polymer film 58 supported by the remaining glass substrate 56.

[0052] Figure 7 demonstrates the possible assemblage 60 of a single freestanding polymer film 62 in a supporting framework 64. The concept of photographic film in the form of slides, i.e. film supported by the surrounding cardboard border frame, is useful to conceptualize the arrangement. The commercial feasibility of a rear polarizer consisting of a freestanding broadband polymer chiral nematic LC film depends on other design parameters, but can be assembled to function as taught herein.

[0053] Figure 8 illustrates yet another configuration 70: multiple film layers 72, 74, 76 each of respectively different, moderate birefringence materials can be fused in order to achieve full spectrum transmission and a single glass substrate 78 can provide support as previously shown in Fig. 4.

[0054] While multifilm polymer chiral nematic LC polarizers can be freestanding, in light of present technological constraints, it is advisable to retain at least one glass support substrate. In the case of multifilm polymer chiral nematic LCs, the elimination of pairs of glass plates and the edging which from the cells required for containing monomeric polarizers, results in a tremendous reduction in bulk. In portable (battery-operated) equipment, the weight savings can then be further increased by reducing the size of the battery, since the power is lessened by the increased transmission efficiency. Alternatively, the power savings can be translated into longer battery time.

[0055] Thus, there has been shown and described a novel polarizer for a liquid crystal display. By using polymer chiral nematic liquid crystal with high birefringence, one gets a broadband polarizer which transmits light without loss. Light outside the bandwidth is transmitted without polarization. Light within the bandwidth is transmitted as circularly polarized light, with virtually no absorption.

[0056] A circular to linear polarizer (such as a quarter wave plate) applies the linearly polarized light within the selected bandwidth to the LCD, which can selectively transmit or block that component in conjunction with a front polarizer. Other modifications and variations will occur to those skilled in the art. Accordingly, the breadth of the invention should be limited only by the scope of the claims appended hereto.

Claims

1. An optical assembly (30) comprising: a light source (12); circular polarizing means in the optical path in a first, forward direction; rear reflecting means (32) adjacent the light source (12) in a second rearward direction; converting means (36) for converting circularly polarized radiation to linearly polarized radiation directly adjacent the circular polarizing means; display means adjacent the converting means for converting linearly polarized light to a direct view display image; and polarization means (20) adjacent the display means for absorbing radiation not contributing to the direct view display image, characterised in that the assembly is a direct view assembly, and the circular polarizing means includes a polymer chiral nematic liquid crystal with a notch polarization bandwidth sufficient to allow transmission of circularly polarized light within a 100 nm to 250 nm wide band.
2. An assembly as claimed in claim 1, wherein the polymer chiral nematic liquid crystal comprises combinations of chiral and nematic liquid crystal monomers attached to backbones selected from the methacrylate/acrylate class of polymers.
3. An assembly as claimed in claim 2, wherein the combinations exhibit birefringence characteristics of cyanotolane and (s)-(-)-1-phenylethanol.
4. An assembly as claimed in any one of the preceding claims, wherein the circular polarizing means includes a polymer chiral nematic liquid crystal configured as a film with less than full surface contact substrate support.
5. An assembly as claimed in any one of the preceding Claims, wherein the polymer chiral nematic liquid crystal is supported through full surface contact with one or more substrates.
6. An assembly as claimed in any one of the preceding claims, wherein the rear reflecting means (32) includes a material which reverses the handedness of circular polarization of some portion of impinging light reflected from the circular polarizing means and which scavenges and returns to the circular polarizing means light from the light source which initially travelled in a direction away from the circular polarizing means.
7. An assembly as claimed in a one of the preceding claims, wherein the rear reflecting means (32) includes a metallic element.
8. An assembly as claimed in any one of claims 5-7 when dependent upon claim 4, wherein the polymer

chiral nematic liquid crystal film is designed with birefringence and notch bandwidth sufficient to circularly polarize and transmit the entire visible light spectrum.

9. An assembly as claimed in claim 1, further comprising a liquid crystal device (LCD), wherein substantially all radiation from the light source within the selected bandwidth is ultimately converted by the polarizer to linearly polarized light which displays the liquid crystal device display image.
10. An assembly as claimed in any one of the preceding claims, wherein the circular polarizing means comprises a plurality of chiral nematic liquid crystal films.

Patentansprüche

1. Optische Anordnung (30), umfassend;

eine Lichtquelle (12);
 eine Zirkularpolarisatoreinrichtung in dem optischen Weg in einer vorwärts orientierten ersten Richtung;
 eine rückwärtige Reflexionseinrichtung (32), die in einer rückwärts orientierten zweiten Richtung benachbart zu der Lichtquelle (12) angeordnet ist;
 eine Umwandlungseinrichtung (36) zum Umwandeln von zirkular polarisierter Strahlung in linear polarisierte Strahlung direkt benachbart zu der Zirkularpolarisatoreinrichtung;
 eine Anzeigeeinrichtung benachbart zu der Umwandlungseinrichtung, um linear polarisiertes Licht in ein Direktblick-Anzeigebild umzuwandeln, und eine Polarisierungseinrichtung (20) benachbart zu der Anzeigeeinrichtung, um Strahlung zu absorbieren, die nicht zu dem Direktblick-Anzeigebild beiträgt, dadurch gekennzeichnet, daß die Anordnung eine Direktblick-Anordnung ist und die Zirkularpolarisatoreinrichtung einen chiralen nematischen Polymer-Flüssigkristall mit einer Polarisationskerbbandbreite umfaßt, die ausreichend ist, die Transmission von zirkular polarisiertem Licht innerhalb eines 100 nm bis 250 nm breiten Bands zu erlauben.

2. Anordnung nach Anspruch 1, worin der chirale nematische Polymer-Flüssigkristall Kombinationen von chiralen und nematischen Flüssigkristallmonomeren umfaßt, die an aus der Methakrylat/Akrylatklasse von Polymeren ausgewählten Stützstrukturen angebracht sind.
3. Anordnung nach Anspruch 2, worin die Kombina-

tionen Doppelbrechungseigenschaften von Cyantolan und (S)-(-)-1-Phenylethanol zeigen.

4. Anordnung nach einem der vorangehenden Ansprüche, worin die Zirkularpolarisatoreinrichtung einen chiralen nematischen Polymer-Flüssigkristall umfaßt, der als ein Film mit weniger als vollflächigem Kontakt zu einer Substrathalterung ausgebildet ist.
5. Anordnung nach einem der vorangehenden Ansprüche, worin der chirale nematische Polymer-Flüssigkristall durch vollflächigen Kontakt mit einem oder mehreren Substraten gehalten ist.
6. Anordnung nach einem der vorangehenden Ansprüche, worin die rückwärtige Reflexionseinrichtung (32) ein Material umfaßt, welches die Händigkeit von zirkularer Polarisatin eines Teils des auffallenden, von der Zirkularpolarisatoreinrichtung reflektierten Lichts umkehrt und welche Licht von der Lichtquelle, das anfänglich in eine Richtung weg von der Zirkularpolarisatoreinrichtung verlief, ausdünn und zurückwirft.
7. Anordnung nach einem der vorangehenden Ansprüche, worin die rückwärtige Reflexionseinrichtung (32) ein metallisches Element umfaßt.
8. Anordnung nach einem der Ansprüche 5 bis 7 in Verbindung mit Anspruch 4, worin der chirale nematische Polymer-Flüssigkristallfilm mit einer Doppelbrechung und einer Kerbbandbreite ausgelegt ist, die ausreichend ist, um das gesamte Spektrum des sichtbaren Lichts zirkular zu polarisieren und zu transmittieren.
9. Anordnung nach Anspruch 1, ferner umfassend eine Flüssigkristallvorrichtung (LCD), worin im wesentlichen alle Strahlung von der Lichtquelle innerhalb der ausgewählten Bandbreite schließlich durch den Polarisator in linear polarisiertes Licht umgewandelt wird, welches das Flüssigkristallvorrichtungsanzeigebild anzeigt.
10. Anordnung nach einem der vorangehenden Ansprüche, worin die zirkulare Polarisatoreinrichtung eine Mehrzahl von chiralen nematischen Flüssigkristallfilmen umfaßt.

Revendications

1. Ensemble optique (30) comprenant : une source lumineuse (12); un moyen de polarisation circulaire dans le trajet optique dans une première direction avant; un moyen de réflexion arrière (32) adjacent à la source lumineuse (12) dans une deuxième di-

rection arrière; un moyen de conversion (36) pour convertir le rayonnement à polarisation circulaire en rayonnement à polarisation linéaire, directement adjacent au moyen de polarisation circulaire; un moyen de visualisation adjacent au moyen de conversion pour convertir la lumière à polarisation linéaire en une image de visualisation pour vision directe, et un moyen de polarisation (20) adjacent au moyen de visualisation pour absorber un rayonnement ne contribuant pas à l'image de visualisation pour vision directe, caractérisé en ce que l'ensemble est un ensemble à vision directe, et en ce que le moyen de polarisation circulaire comprend un cristal liquide polymère chiral nématique présentant une largeur de bande de polarisation d'encoche suffisante pour permettre la transmission de lumière à polarisation circulaire dans les limites d'une bande d'une largeur de 100 nm à 250 nm.

2. Ensemble suivant la revendication 1, dans lequel le cristal liquide polymère chiral nématique comprend des combinaisons de monomères de cristal liquide chiral et nématique fixés aux charpentes sélectionnées dans la catégorie méthacrylate/acrylate des polymères.
3. Ensemble suivant la revendication 2, dans lequel les combinaisons présentent des caractéristiques de biréfringence du cyanotolane et du (s)-(-)-1-phényléthanol.
4. Ensemble suivant l'une quelconque des revendications précédentes, dans lequel le moyen de polarisation circulaire comprend un cristal liquide polymère chiral nématique configuré sous la forme d'un film présentant un support de substrat dont le contact n'est pas réalisé sur la totalité de la surface.
5. Ensemble suivant l'une quelconque des revendications précédentes, dans lequel le cristal liquide polymère chiral nématique est supporté par contact avec un ou plusieurs substrats sur la totalité de la surface.
6. Ensemble suivant l'une quelconque des revendications précédentes, dans lequel le moyen de réflexion arrière (32) comprend un matériau qui inverse la symétrie de la polarisation circulaire d'une certaine partie de la lumière incidente réfléchie à partir du moyen de polarisation circulaire et qui absorbe et restitue au moyen de polarisation circulaire la lumière de la source lumineuse qui à l'origine se déplaçait dans une direction opposée au moyen de polarisation circulaire.
7. Ensemble suivant l'une quelconque des revendications précédentes, dans lequel le moyen de réflexion arrière (32) comprend un élément métalli-

que.

8. Ensemble suivant l'une quelconque des revendications 5 à 7 lorsque dépendantes de la revendication 4, dans lequel le film de cristal liquide polymère chiral nématique est conçu avec une biréfringence et une largeur de bande d'encoche suffisantes pour polariser de manière circulaire et transmettre tout le spectre de la lumière visible.
9. Ensemble suivant la revendication 1, comprenant en outre un dispositif à cristaux liquides (LCD), dans lequel pratiquement tout le rayonnement de la source lumineuse, dans les limites de la largeur de bande sélectionnée, est finalement converti par le polariseur en lumière à polarisation linéaire qui visualise l'image de visualisation du dispositif à cristaux liquides.
10. Ensemble suivant l'une quelconque des revendications précédentes, dans lequel le moyen de polarisation circulaire comprend une pluralité de films de cristal liquide chiral nématique.




FIG. 1





FIG. 2A

FIG. 2B







FIG. 3
PRIOR ART

10



30

FIG. 4A




FIG. 4B




FIG. 5
PRIOR ART




FIG. 6A

FIG. 6B




FIG. 7




FIG. 8

